

HX-24E

LED-backlit Display

Monitor High-Definition,
Real-time Video
with Zero Latency



- Anti-Burn-in
- NeoV™ OPTICAL GLASS
- HD-SDI
- 24/7

The HX-24E offers native Full HD resolution with high contrast ratio, wide viewing angles and consistency of picture quality. The HX-24E is built to survive the rigors of production in studios and surveillance environments, the solid protection of a metal enclosure housing the NeoV™ Optical Glass and Anti-Burn-in™ technology makes it a fitting choice for a full spectrum of professional applications that require 24/7 nonstop operation.






Superb Image Quality Guaranteed

Selectable gamma curve visually optimizes different kinds of images. The AG Neovo specialized image settings enhance colour, brightness, sharpness and contrast ratio, allowing the HX-24E to improve the light, shadows and colour balance of videos.

Automatic SDI Switching

HX-24E has been designed for broadcasting as well as surveillance and includes support for multiple SDI video standards, including SD, HD and 3G-SDI formats. All video formats can be connected and changed at any time, the HX-24E will automatically switch to the new format.



Easy to Connect

The HX-24E offers a wide variety of inputs for compatibility with the majority of video and data sources. Its high-quality HD-SDI input and loop through HD-SDI output makes it easy to connect other gear without the need for a splitter.

Industry-leading Reliability

The HX-24E is specially designed to transcend the challenge of enduring 24/7 operations. AG Neovo's Anti-Burn-in™ technology also prevents image ghosting while performing nonstop mission-critical operations. Its metal casing and NeoV™ Optical Glass not only protect the HX-24E from damage but also keep maintenance easy.



Features

- Full HD 1920 x 1080 resolution
- Supports multiple SDI formats: 3G/HD/SD-SDI
- Embedded audio in SDI up to 8 channels of 48kHz
- Anti-Burn-in™ technology prevents image ghosting
- NeoV™ Optical Glass and metal housing for excellent cleanability and protection
- VA panel technology ensures accurate colours and offers high contrast ratios with wide viewing angles
- Image enhancer: 3D Comb Filter / Deinterlace / Noise Reduction
- Versatile connectivity: 3G SDI, DisplayPort, HDMI, DVI, VGA, Composite
- SDI and Composite loop-through output port
- EcoSmart Sensor automatically adjusts brightness level according to ambient lighting conditions
- Selectable gamma curves optimise different kinds of images
- Designed and developed for continuous 24/7 operation



Specifications

HX-24E

Panel	Panel Type Panel Size Max. Resolution Pixel Pitch Brightness Contrast Ratio Viewing Angle (H/V) Display Colour Response Time Surface Treatment	LED-Backlit TFT LCD (VA Technology) 23.6" FHD 1920 x 1080 0.272 mm 250 cd/m ² 20,000,000:1 (DCR) 178°/178° 16.7M 5 ms Anti-Glare Treatment (Haze 25%),3H Hard Coating
Frequency (H/V)	H Freq. V Freq.	24 kHz-83 kHz 50 Hz-75 Hz
Input	SDI DisplayPort HDMI DVI VGA Composite	BNC x 1 x 1 1.4 x 1 24-Pin DVI-D x 1 15-Pin D-Sub x 1 BNC x 1
Output	SDI Composite	BNC x 1 BNC x 1
External Control	RS232 in/out	2.5 mm Phone Jack
Other Connectivity	USB	2.0 x 1 (Service Port)
Audio	Audio In Internal Speakers	Stereo Audio Jack (3.5 mm) Stereo Audio Jack (RCA) 2W x 2
SDI	3G-SDI (SMPTE 424M) HD-SDI (SMPTE 292M) SD-SDI (SMPTE 259M)	1080p @50/60fps 720p @25/30/50/60fps, 1080p @24/25/30/50/60fps 1080i @50/60fps 480i @60fps, 576i @50fps
Power	Power Supply Power Requirements On Mode Stand-by Mode Off Mode	External DC 12V, 2.5A 22W (On) < 0.5W < 0.5W
NeoV™ Optical Glass	Thickness Reflection Rate Transmission Rate Hardness	3.0 mm (0.12") < 1% > 97% > 9H
Operating Conditions	Temperature Humidity	0°C-40°C (32°F-104°F) 10%-90% (non-condensing)
Storage Conditions	Temperature Humidity	-20°C-60°C (-4°F-140°F) 5%-95% (non-condensing)
Mounting	VESA FPMPI	Yes (100 x 100 mm & 75 x 75 mm)
Stand	Tilt	0° to 15°
Security	Kensington Security Slot	Yes
Dimensions	w/Base (W x H x D) w/o Base (W x H x D) Packaging (W x H x D)	562.4 x 396.8 x 155.0 mm (22.1" x 15.6" x 6.1") 562.4 x 352.6 x 56.2 mm (22.1" x 13.9" x 2.2") 662.0 x 511.0 x 210.0 mm (26.0" x 20.1" x 8.3")
Weight	w/Base w/o Base Packaging	7.9 kg (17.4 lb) 7.3 kg (16.0 lb) 9.9 kg (21.8 lb)
Regulation Approval	Certifications & Compliance	CE, LVD, WEEE, RoHS, REACH, EAC
Accessories	Supplied	Power Adaptor, Power Cord, VGA Cable, Audio Cable, Quick Start Guide, Warranty Card
Optional Accessories		Wall Mount: PMK-01 Desk Mounts: DMC-01, DMC-02D, DMS-01D, DMS-01Q, ES-02 Ceiling Mount (Landscape only): CMP-01 + WMK-03 Wall Mounts (Landscape only): WMA-01, WMK-01, WMK-03

Global Headquarters

Taipei, Taiwan

EMEA Regional Headquarters

Capelle a/d IJssel, The Netherlands

North & South America Regional Headquarters

San Jose, CA, U.S.A.

Asia-Pacific Regional Headquarters

Taipei, Taiwan

Canada Sales Office

Vancouver, B.C., Canada

China Sales Office

Shanghai, China

Czech Republic Sales Office

Brno, Czech Republic

Denmark Sales Office

Støvring, Denmark

Germany Sales Office

Mechernich, Germany

Italy Sales Office

Livorno, Italy

Poland Sales Office

Warsaw, Poland

Spain Sales Office

Barcelona, Spain

Ukraine Sales Office

Lviv, Ukraine

displays.agneovo.com