

DH-NKB1000/DH-KBD1000/DH-KB1000

Network Keyboard & Control Keyboard & Dome keyboard



Features

- Keyboard to Control
- -Dahua High Speed Dome (all models)
- -Dahua Standalone DVR (KBD1000 & NKB1000 only)
- -Dahua Network High Speed Dome (NKB1000 only)
- -Network Video Server (NKB1000 only)
- Connection
- -NKB1000: RS485, RS422, USB, RS232 & Network
- -KBD1000: RS485, RS422, USB & RS232
- -KB1000 : RS485, RS422 & USB
- Three Dimensional Joystick Control of PTZ Functions
- Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Control
- Auxiliary Functions
- On-Screen Menu & User Operation Procedure Tips
- Connect to SmartPSS via USB (NKB1000 only)

Technical Specifications

Model	DH-NKB1000	DH-KBD1000	DH-KB1000
General			
Keyboard Keypanel	Electromechanical		
Joystick	3-axis, vector-solving, with twisting, return to-center head		

DH-NKB1000/DH-KBD1000/DH-KB1000

Keyboard Connector	RJ-45,RS232,RS485,RS422,USB,	RS232,RS485,RS422	RS485,RS422
Keyboard Communication	Direct Mode, Network Mode	Direct Mode	Direct Mode
Direct Mode	Interface: RS232/RS485 DVR Protocol: DH2 Dome Protocol: DH-SD/PELCO-D/PELCO-P/PELCO-D1/PELCO-P1.....		
Network Mode	Interface: RJ45 DVR/Network Dome: IP Address/Port/Protocol	N/A	N/A
Display	LCD, 75.2mm x 33.85mm		
Environmental			
Power Supply	Power adapter, input 100V~240V 50Hz / 60Hz,output DC12V/1000mA		
Power Consumption	5W		
Working Temperature	-10℃ ~ +55℃		
Working Humidity	10%~90%		
Atmosphere Pressure	86kpa~106kpa		
Dimension	330mmx160(140)mmx37.5(21)mm (W×D×H) (height: 100mm including joystick)		
Weight	2.5KG		

Dahua Technology Co., Ltd.

1187 BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email:overseas@dahuatech.com

www.dahuatech.com

*Design and specifications are subject to change without notice.

© 2013 Dahua Technology Co., Ltd.